

TITLE OF THE INVENTION

SPORTS EQUIPMENT BAG, ORGANIZER AND VENTILATOR

CLAIM OF PRIORITY

[0001] This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. §119 from a provisional application entitled *Sports Equipment Bag- Organizer and Ventilator* earlier filed under 35 U.S.C. §111(b) in the United States Patent and Trademark Office on 14 December 2000 and there duly assigned Serial No. 60/255,060, and a disclosure document entitled *Sports Equipment Organizer with Locking Device* on 22 March 2001 and there duly assigned Disclosure Document No. 490860.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to a sports equipment bag, and more particularly, to a bag for organizing sports equipment and related articles while providing ventilation for the sports equipment and the related articles.

Description of the Background Art

[0003] In athletic activities such as hockey, baseball, football, or inline skating, a person may have to carry uniforms, a face mask, helmets, knee pads, and other assorted sports equipment. The

1 assorted equipment have usually been just placed in a bag where it has been difficult to take out the
2 sometimes heavy and cumbersome equipment and also to perform a visual inventory of the bag.
3 Another problem with the earlier sports equipment bags was that the equipment and clothing articles
4 related to the sports accumulated perspiration. The bag would cause an increased odor because of
5 the lack of proper ventilation. The damp garment, sports, and athletic equipment, boots and shoes
6 were dried out on purchased racks or spread around on the floor or on furniture. Garments and
7 sports equipment that retain water will mold, mildew, and develop unpleasant odors without
8 adequate air circulation. Equipment in a bag should be dried out, so there is an aggravation of
9 removing equipment from the bag to dry the equipment because if the equipment is left in the bag,
10 there can be damage to equipment if the equipment cannot fully dry. It is a cumbersome process of
11 taking the equipment out of the bag. Unloading the conventional sports bag and placing the items
12 around an area to allow for air-drying is time consuming, visually unpleasant, and consumes space.
13 This procedure also increases the chance of misplacing an item and leaving it behind.
14 Conventionally vented bags offer limited benefit due to the density of equipment obstructing air
15 penetration inside the bag.

16 **[0004]** A travel and sports organizer bag, equipped with a method of air circulation is needed to
17 effectively air dry articles without complex and expensive structures as well as being an organization
18 and space saving tool that allows for quick and easy use.

19 **SUMMARY OF THE INVENTION**

20 **[0005]** It is therefore an object to have a bag that can effectively air dry articles without complex

1 and expensive structures as well as being an organization and space saving tool.

2 **[0006]** It is another object to have a bag that can have the contents viewed quickly for use.

3 **[0007]** It is yet another object to have a bag that can be locked quickly to a locker without
4 extensive extra parts.

5 **[0008]** It is still yet another object to have a bag that can ventilate while being in a closed position.

6 **[0009]** It is yet another object to have a bag that can ventilate while being in an open or folded
7 position.

8 **[0010]** It is another object to have a bag that can be easily hung up to allow a flat view of the
9 contents.

10 **[0011]** It is yet another object to save time by being able to hang up all contents of a bag at the
11 same time.

12 **[0012]** It is still another object to have a bag that can organize objects in a bag in a systematic
13 manner.

14 **[0013]** It is another object to have objects organized in a single plane.

15 **[0014]** To accomplish the above and other objectives, the present invention provides a bag
16 including a back wall having a hook accommodating the hanging of the bag when opened, a plurality
17 of compartments on a front surface of the back wall, the plurality of compartments having a front
18 portion being of a mesh or netted material accommodating a view of the objects and a circulation
19 of air within the compartments. The compartments can have shelves projecting from the back wall
20 to accommodate the objects. The wall can be folded or rolled to close the back wall into the bag for
21 carrying by the handles through hands or on a back of a user. The bag may include a locking bar or

1 another object designed to prevent removal of the bag (connection accommodating the bag to lock)
2 on a zipper enclosing the bag that can be used to secure the bag to a locker.

3 **BRIEF DESCRIPTION OF THE DRAWINGS**

4 [0015] A more complete appreciation of this invention, and many of the attendant advantages
5 thereof, will be readily apparent as the same becomes better understood by reference to the following
6 detailed description when considered in conjunction with the accompanying drawings in which like
reference symbols indicate the same or similar components, wherein:

7 [0016] Fig. 1 is a perspective view of the object holder of a bag in an opened flat position; ✓

8 [0017] Fig. 2 is a view of a bag having the object holder of Fig. 1 folded up and having handles
9 for hand carrying;

10 [0018] Fig. 3 is a view of a bag having straps attached to the object holder of Fig. 1 folded to
11 provide a backpack; ✓

12 [0019] Fig. 4 is view of another embodiment having the object holder of Fig. 1 connected to the
13 inside portion of a container portion of the bag; ✓

14 [0020] Fig. 5 is a plan view of an object holder of another embodiment in an opened position;

15 [0021] Fig. 6 is a plan view of the object holder of Fig. 5 in a closed position and secured to a
16 locker;

17 [0022] Fig. 7 is a perspective view of a backpack having the object holder in a closed position;

18 [0023] Fig. 8 is another embodiment of a backpack in an open position;

19 [0024] Fig. 9 is another embodiment of a handbag in an open position;

- 1 6^(a) [0025] Fig. 10 is the backpack of Fig. 8 in a closed position;
- 2 7^(b) [0026] Fig. 11 is a strap of the backpack of Fig. 8; /
- 3 8 [0027] Fig. 12 is a plan view of the bag of Fig. 5 in an open position;
- 4 9 [0028] Fig. 13 is another embodiment of the opening of the bag of Fig. 5;
- 5 10 [0029] Fig. 14 is a view of a loop in the bag of Fig. 5; /
- 6 11 [0030] Fig. 15 is a plan view of the backpack of Fig. 8 having wheels;
- 7 12 [0031] Fig. 16 is a view of the bag of Fig. 9 in the closed position with loops for attaching hanging
hook for secure closing;
- 8 13 [0032] Fig. 17 is view of the backpack of Fig. 10 having a mesh sidewall;
- 9 14 [0033] Fig. 18 is a view of a bag folded in reverse; and
- 10 15 [0034] Fig. 19 is a view of a bag accommodating longer items.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

13 [0035] Turning now to the drawings, as seen in Fig. 1, an object holder 10 can be hung by a hook
14 12 on to a locker or other stationary area so that the equipment and other articles can be easily seen
15 and used. The object holder 10 can be a bag itself or an insert within another bag. The object holder
16 10 does not necessarily have to hang vertically or hang at all. The object holder 10 can also be
17 positioned on top of a bench or on a floor horizontally to allow for access to the equipment or any
18 other position where the equipment or objects held by the object holder 10 can be viewed. Objects
19 such as sports equipment, clothing, shoes, boots, ice skates, ski boots, and other objects can be
20 placed in the different compartments of the object holder 10.

1 [0036] The object holder 10 can be made of canvas, vinyl such as PVC (polyvinyl chloride),
2 plastic, other types of polyester or fabric material that allows for folding or rolling up for storage.
3 The object holder 10 can be made of flexible material.

4 [0037] The compartments, or chambers are built into the object holder 10 to accommodate objects
5 to be organized and dried. The chambers or compartments can be expanded to accommodate the
6 articles. One or more zippers 22 or a hook 12 and loop 120, releasable fasteners 34 or velcro along
7 the top of the bag function to close the bag and allow access into the bag chambers to facilitate the
8 introduction of articles into the bag chamber and removal of the articles from the bag. In Fig. 1 for
9 example, a mouth piece 18 is placed in the upper left compartment 20, while the upper right
10 compartment 26 can hold articles such as a puck 24. Both the upper left 20 and upper right 26
11 compartments can be closed by using zippers 22. Other types of devices other than zippers 22 may
12 be used to close the top compartments. Since the articles are small, the zippers or other similar
13 fasteners help to close the upper left and right compartments 20 and 26.

14 [0038] A third compartment 30 below the upper compartments 22 and 26 may have equipment
15 such as hockey gloves 32. The third compartment 30 may have fasteners 34 allowing for quick
16 access to the hockey gloves 32. A clasp or other fastener 34 can be sufficient for holding the items
17 because when folded, the pressure of the items will hold the items in place. Elastic bands may be
18 used with the snap fasteners 34 to allow for the pocket to be stretched out while placing equipment
19 inside. A portion or all of top border 36 can be of an elastic or resilient material. Velcro may also
20 be used in place of the snap fasteners 34. The top border area 36 which is open for access to the
21 gloves 32 when the fastener 34 is open. However, when the fastener 34 is closed, the top border area

1 36 is pulled closer to the back portion or wall 16, thereby preventing articles such as the gloves 32
2 from releasing from the third compartment 30. The bag can be without fastener 34 because once the
3 bag is closed, the pressure of the equipment or gear against each other can prevent articles from
4 falling out.

5 **[0039]** A fourth compartment 38 disposed below the third compartment 30 is made similar to the
6 third compartment 30. A mesh (netted) material 14 is stitched or connected in some other manner
7 to the border material 40. The border material 40 can be stitched or through another method
8 connected with the back wall 16 of the object holder 10 made of material such as canvas. The upper
9 border material 42 is not connected to the back wall 16, thus allowing access to equipment within
10 the compartment. The compartments can be varied in terms of the size, quantity and location within
11 the bag depending on the sport or activity.

12 **[0040]** The mesh (netted) material 14 allows for a person to easily locate an equipment item and
13 the mesh also provides for ventilation of the articles. The partially see-through material allows for
14 a fast inventory to confirm that all gear needed is packed. The object holder 10 may either be hung
15 up for ventilation or positioned at any angles such as horizontal to the ground such as on a bench or
16 ground. The object holder 10 just needs to be in the open position as shown in Fig. 1, allowing for
17 exposure of the equipment through the mesh material 14. Materials other than mesh 14 can be used
18 in the alternative such as any other material that allows for ventilation and visibility of equipment
19 stored within the compartment. The mesh material allows the air to be exhausted from the
20 compartments through the air vents.

21 **[0041]** A fifth compartment 44 below the fourth compartment can have a plurality of sub-

1 compartments that can hold various smaller equipment. The fifth compartment holds smaller items
 2 and materials relatively flat and allows the bag to fold over. A sixth compartment 46 below the fifth
 3 compartment 44 can be substantially V-shaped or U-shaped having for example a flat portion 48
 4 truncating the vertex of the V-shaped fifth compartment 46. The V-shaped compartment 46 or
 5 pocket provides for a helmet 50 or other large object such as a soccer ball that can fit for example
 6 between the skates 52 or boots. The V-shape accommodates an efficient use of space and allows for
 7 the object holder 10 to sit evenly for easier storage. The helmet 50 sits snugly between the pair of
 8 skates allowing not only efficient and easy access, but also better ventilation. Multiple equipment
 9 items are not on top of each other to prevent the efficient drying of wet equipment. The middle
 10 section such as the fifth compartment 44 needs to be smaller so that it holds smaller items
 11 accommodating an easier closing of the bag. The middle section 44 can also be flat to accommodate
 12 an easier closing of the bag.

13 **[0042]** In the seventh compartment 54, the in-line skates 60 or some other pair of boots, are
 14 positioned on each end with a top portion 58 of the compartment and the side portions 56 of the
 15 compartment 54 being closed. The side portions 56 are not made of a mesh material but of a solid
 16 see-through material or a solid material that is not see-through so that when the skates for instance
 17 are placed in the seventh compartment 54, the wheels or blades will not wear out the mesh material
 18 prematurely. The open area 62 allows for a better ventilation of the boots, since the opening portion
 19 of the boots is in an open area 62 allowing for free air flow without even the mesh (netted) surface.

20 **[0043]** A horizontal fastener 64 is situated between the left and right side 54a and 54b of the
 21 seventh compartment 54. The horizontal fastener 64 as opposed to the vertically disposed fasteners

1 34 on the other compartments, allow for an efficient access to the boots or inline skates 60. When
2 unattached, the fasteners 64 allow for the top 58 and side portions 56 of the left and right 54a and
3 54b of the seventh compartment 54 to open fully to allow for access to the large boots or skates.
4 Other types of equipment may be organized within the compartments or pockets. Other type of
5 fasteners may also be used.

6 **[0044]** Referring to Fig. 2, the object holder 10 in one embodiment can be folded up or rolled up
7 to form a bag 110 allowing for the object holder 10 to be carried. The rolling or folding also keeps
8 the equipment inside relatively stationary within the bag 110 when the bag 110 is closed. The
9 jiggling of large or small equipment can otherwise cause damage to the equipment and create noise
10 when transporting. The hook 12 or other similar fastening device is detachably connected to a sleeve
11 or loop 120 formed on the back side 140 of the back wall 116 of the object holder 10. Using the hook
12 12 to fasten together the bag 110 helps to avoid adding other components to the bag 110, thereby
13 reducing the cost of manufacture. Other types of fasteners can also be used. The adjustable hooking
14 mechanism 142 including the hook 12 and the adjustment portion 144 attached at the top of the
15 object holder 10 allows a user to hang the bag 110 up to access the objects stored in the bag 110 and
16 allow for air flow into the objects. The adjustable hooking mechanism 142 by adjusting the length
17 of the adjustable strap 146 through the adjustment portion 144, also allows the bag 110 to still
18 ventilate while the bag is in a closed position when the hooking mechanism 142 is connected to the
19 sleeve 120. Although the ventilation in the closed position is much less than when the bag 110 is
20 in the open position. The adjustable strap can provide some air flow into the bag 110 if it is loosened
21 slightly. Even when tightly fastened, some air flow is still allowed through the unattached sides 148

1 of the object holder 10. Air flow is also allowed through the open sides 150 of the bag 110. When
2 the bag 110 is folded, on the left and right sides have open sides 150 to allow for air ventilation. The
3 mesh material 14 of the compartments are also exposed on the open sides 150 to ventilate the bag.
4 Since, the bag has open sides 150 on both sides of the bag, this allows for a cross ventilating airflow
5 that makes the drying more efficient. The bag 110 in an opened position such as when the bag 110
6 is hung or laid flat on a bench is the most efficient method of ventilating and drying the objects held
7 by the bag. However, the structure of the bag also allows for a certain amount of ventilation while
8 the bag is in a closed position such as when the hook 12 is secured to the sleeve 120. The object
9 holder 10 can be laid in any space available such as the back seat or in the trunk of a vehicle while
10 transporting the bag 110. For instance, sports teams may lay the bag 110 on the grass outside for
11 drying. The equipment stays together and is easily returned to the original position for moving to
12 another location. Since the hook 12 is attached to the adjustable strap 146 allowing the bag 110 to
13 be adjusted to rest on the floor for instance, thereby taking the weight off the bag 110 and support.

14 **[0045]** To allow for an efficient way to transport the bag 110, a handle 130 is attached to the back
15 side 140 of the top portion 160 and another handle 130 is attached to the bottom portion 170 of the
16 object holder 10. The handles 130 can for example be attached to the left 130a and right side 130b
17 to the object holder 10 to allow for a user to grasp with a hand both handles 130 so that the bag 110
18 can be transported. Referring to Fig. 18, the bag can be folded in reverse with the compartments on
19 the outside allowing for ventilation.

20 **[0046]** The top portion 160 can for example overlap the bottom side 170 of the object holder 10
21 in order to fasten the bag together. The opposite arrangement can also be true where the bottom

1 portion 170 overlaps the top portion 160. In another arrangement, neither the top portion 160 or the
 2 bottom portion 170 overlaps each other. Other types of securing mechanisms can be used to close
 3 the bag 110 such as a zipper or other types of fasteners. The bag 110 can also have a shoulder strap
 4 162.

5 **[0047]** In another embodiment of the present invention, as seen in Fig. 3, the object holder 10 can
 6 be folded to form backpack or bag 210 allowing a user to have one or both handles 220 supported
 7 on the shoulders of a user. For example, the top portion 160 can be folded to meet with the bottom
 8 portion 170 of the object holder 10 to connect the two sides using the adjustment strap 146. The
 9 backpack 210 can be connected in the same way as in seen by the bag 110 or in some other similar
 10 fashion allowing for the adjustment connection between the top portion 160 and bottom portion, or
 11 no adjustment, but just a connection between the two portions of the object holder 10. The pair of
 12 handles 220 can for example be placed on one side of the object holder on opposite ends of the back
 13 side 140 of the object holder. The position of the handles are such that a user can carry the backpack
 14 210 on both shoulders at the same time if needed. The top portion 220a of the handle 220 is coupled
 15 on the top portion of the backpack 210 and the bottom portion 220b of the handle 220 is positioned
 16 below the top portion 220a of the handle 220. Other configurations of the handles 220 can be made
 17 as long as a user may carry the bag 210 on both shoulders at the same time. A V-shaped
 18 compartment such as the sixth compartment 46 is not preferable in a the backpack 210 when the
 19 backpack 210 is typically more narrow in shape.

20 **[0048]** In another embodiment of the present invention, as seen in Fig. 4, the object holder 10 has
 21 a bottom portion 170 connected to an internal section 314 of a container portion 330 to form a bag

1 310. The container portion 330 can be for example be rectangular in shape with a top portion 340
2 cut out into a flap 320 that can close the compartment 350 within the container portion 330. The flap
3 320 for example may close the container portion 330 by a zipper for example or other similar device.
4 When the flap portion 320 is unattached from the container portion 330, the object holder 10 can be
5 raised out of the container portion 330 allowing the object holder 10 to be hung by the hook 12 or
6 laid flat on a surface. The container portion 330 allows for a convenient storage or hanging of the
7 object holder 10. The container portion 330 also provides for further storage of items. The container
8 portion can be have a rectangular shape or any other type of shape depending on the use and size of
9 the objects.

10
11
12
13
14
15
16
17
18
19
20
21
[0049] In another embodiment of the present invention, as seen in Fig. 5, the object holder 420
can have a portion such as the bottom portion 470 have shelves that project out of the back wall 440.
The object holder 420 when opened can be hooked to locker hook 414 for example or any other
location that can support a hook 412. A first compartment 424 can be closed with a zipper 426 to
hold a variety of objects. A mirror 428 just below the first compartment 424 is added for uses such
as applying make-up, tying a man's tie, or other uses where a mirror is appropriate. Below the
mirror 428 is a second compartment 448 holding objects in a vertical position with respect to the
vertically hung bag 410. Objects such as toiletries such as shampoo and conditioner may be inserted
into the second compartment 448 through an opening in the upper portion 448a. The compartment
may or may not be of a mesh (netted) or see-through material allowing for a quick view of the
internal objects and also allow for ventilation of the objects.

[0050] A first shelf 442 projects out of the back wall 440. The first shelf 442 has side walls 444

1 and 446 that accommodates the closing of the object holder 420 to form a bag 410. The side walls
 2 444 and 446 and shelf 442 accommodates the width of the objects in the second compartment 448.
 3 The second compartment 448 is located above the first shelf 442 towards the middle portion 464 of
 4 the object holder 420. The first shelf 442 is set back a predetermined distance L_1 to allow the top
 5 portion of the object holder to close the object holder to form a bag 410. The set back of L_1 provides
 6 an even surface of the bag 410 when the bag 410 is closed for transporting as seen in Fig. 6.

7 **[0051]** The left and right side walls 444 and 446 extend from the middle portion 464 to the end
 8 of the bottom portion 470 of the object holder 420. The side walls 444 and 446 accommodate a a
 9 third compartment 450 and a fourth compartment 456. The third compartment is bordered by the
 10 back wall 440 on a back side, the first shelf 442 being a top side, the left and right side walls 444 and
 11 446, and the second shelf 454 as the bottom portion of the third compartment 450. A mesh (netted)
 12 strip 452 is connected from a portion of the left side wall 444 to a portion of the right side wall 446.
 13 The mesh strip 452 is also connected to a second shelf 454. The mesh strip 452 covers only a
 14 portion of the opening of the third compartment 450. The third compartment 450 accommodates
 15 a horizontal loading of objects when the object holder 420 is hanging open vertically. The mesh
 16 strip 452 contains the objects within the third compartment 450 so that the objects will not fall out
 17 of the object holder 420 when the object holder 420 is hung. Since the mesh strip 452 encloses only
 18 a portion of the opening of the third compartment 450, there is easy and quick access for a user to
 19 insert various objects within the compartment. The mesh strip 452 because of the mesh material
 20 accommodates a user to be able to view the contents in their entirety while still allowing for an
 21 increased ventilation of the objects within the third compartment 450. The third shelf 454 is set back

1 in the compartment from the outer edge of the side walls 444 and 446 a predetermined distance
2 similar to the set back of the first shelf. The set back distances can be varied also if needed.

3 **[0052]** The fourth compartment 456 located below the third compartment is constructed in the
4 same manner as the third compartment. The opening of the fourth compartment 456 is partially
5 enclosed by the mesh (netted) strip 458 while the bottom shelf 472 serves as the bottom portion of
6 the fourth compartment and also an end portion of the object holder 420. The third shelf 472 is not
7 set back from the outer edges 444b and 446b of the side walls 444 and 446, respectively like the first
8 and second shelf 442 and 454. However, the mesh strip 458 is set back from the outer edges 444b
9 and 446b to accommodate the closing the bag 410 with the top portion 460 of the object holder 420
10 being folded over in the set back area of L_1 .

11 **[0053]** The top portion 460 of the object holder 420 has a width L_3 much smaller than the width
12 L_2 of the third shelf 472. The thinner top portion 460 then can fold within the set back area of L_1 and
13 fit in gap between the top sides 444a and 446a of the left and right side walls 444 and 446. Then the
14 top portion 460 is folded around the first, second, and third shelves 442, 454, and 472 within the set
15 back width L_1 .

16 **[0054]** A handle 488 is connected on the left side wall 444, and another handle 488 is connected
17 on the right side wall 446 so that when closed, the bag 420 can be easily transported as seen in Fig.
18 6. A zipper 480 for example can be located adjacent to the outer edges 444b and along the top
19 portion 444a of the side wall 444. A second zipper 482 for example can be located adjacent to the
20 outer edges 446b and along the top portion 446a of the side wall 446. The two zippers 480 and 482
21 run the length of the bag 410 to allow the unfolding and hanging of the bag 410 on a hook 414 for

1 example. The two zippers 480 and 482 can also be a single zipper having two sliding parts on each
2 side of the bag closing and opening the interlocking tabs disposed along the length of the bag.

3 **[0055]** The two zippers 480 and 482 have the sliding parts 480a and 482a, respectively, connected
4 together by a locking bar 490. When the bag 410 is closed, the locking bar 490 inside for instance
5 between the doors 510 and the body 520 of a gymnasium locker 500. The locking bar 490 is wider
6 L_4 than the width L_5 of the gymnasium locker 500. The locking bar 490 can also be an object of
7 another shape such that the dimensions of the object exceed the opening dimensions between the
8 door and the locker once the locker is closed. For example, when the object is spherical, the
9 diameter exceeds the opening distance "d" between the door 510 and the body 520 of the locker 500,
10 so that the object cannot be removed from the closed locker. Once, the gymnasium locker 500 is
11 secured by for instance a lock 530, the bag 410 is held in place by the locked door 510. A thief will
12 not be able to pick up the bag 410 without having to rip open the bag 410. When the bag 410 is in
13 the closed position as shown in Fig. 6, the bag itself may be secured, such that when the bag 410 has
14 the locking bar 490 within the gymnasium locker 500, the bag 410 cannot be opened. This allows
15 a user to have open access to bag 410 even when the locker 500 is closed without having to worry
16 about if someone will steal the bag. The locking bar 490 also allows a user to not have to shove the
17 bag within the locker 500. The bag 410 with the locking bar 490 can be opened and locked without
18 having to move the bag. Furthermore, if the bag 410 is larger than the locker 500, it can still be
19 securely used by being placed outside of the locker 500. Further, since the bag 410 can be placed
20 outside of the locker 500, then more room is allowed within the locker 500 to store other objects.
21 The bag 410 can be secured quickly to the locker 500 without having to add an extra securing

1 mechanism. When the locker 500 is opened, a user can take the bag 410 with them.

2 **[0056]** The locking bar 490 can be made adjustable to accommodate different sizes of lockers 500.

3 **[0057]** The bag 410, which can be used for gymnasium activities for example, may have a plastic
4 liner included to store wet clothing or a bathing suit. The bag 410 can have the zipper 492 along the
5 edges of the walls open up with the side walls being on the bottom portion as seen in Fig. 12 or as
6 seen in Fig. 13, the zipper 495 opens the bag having the side walls 494 being on the top portion
7 where the top portion can be hooked to an door or shelf. As seen in Fig. 14, a loop 498 at the top
8 of the bag allows hangers of clothes to be attached.

9 **[0058]** The object holder 420 as seen in Fig. 5, can also be enclosed as seen in the bag of 610 as
10 seen in Fig. 7. The bag 610 has an object holder such as the object holder 420 or the object holder
11 10. The object holder 620 has a pair of handles along the length of one side on the back wall 640 of
12 the object holder 620. The handles 688 allow a user to carry the bag 610 around both shoulders on
13 their back like a backpack. A zipper 680 or other connector type closes the bag 610. Additional
14 pockets 630 may be added to the outside of the bag 610 to allow additional storage and quicker
15 access when the bag 610 is closed.

16 **[0059]** A backpack 710, as seen in Fig. 8 has a hook 712 that is shaped to hang on top of a door.
17 The hook 712 is attached to a strap 713 that allows the bag to rest on the floor, thereby reducing the
18 weight on the hanging structure. A clasp 714 are attached on the pockets 770 to help secure items
19 inside. The clasp 714 can be substituted with velcro or other similar means. Elastic is sewn into
20 the strap 716 to keep the strap 716 at the top of each compartment straight and assist in securing the
21 items in the compartments. Smaller items are stored in the middle compartments 718 and are

1 structured to allow the top to fold down smoothly. Side handles 720 are sewn into the side walls 724
2 to accommodate additional carrying options. A mesh wall 722 is used to hold any smaller items in
3 the bottom and the wall 722 assists in holding the sides together.

4 **[0060]** In another embodiment, as seen in Fig. 9, the handbag 810 has a hook 812 for hanging on
5 top of a door or other stationary structure. The hook 812 is attached to a strap 813 that allows the
6 bag to rest on the floor, thereby reducing the weight on the hanging structure. A clasp 814 are
7 attached on the compartments 870 to help secure items inside. The clasp 814 can be substituted with
8 velcro or other similar means. Elastic is sewn into the strap 816 to keep the strap 816 at the top of
9 each compartment straight and assist in securing the items in the compartments. Smaller items are
10 stored in the middle compartments 818 and are structured to allow the top to fold down smoothly.
11 Handles 828 are connected to the top and bottom portions of the bag to accommodate the carrying
12 of the bag 810. An adjustable strap 830 can hold additional items or hold in place items such as
13 clothes. Referring to Fig. 16, the bag 810 has a webbing attached to the outside of the bag 810 to
14 allow securing of the hook 812 and holding the bag closed.

15 **[0061]** As seen in Fig. 10, the backpack 710 is in a closed position. The backpack 710 has a top
16 mesh pocket 732 and a bottom mesh pocket 730. Each of the pockets has only a portion that is made
17 of mesh material and the remaining portion of the pockets being of solid material that is not see-
18 through. Solid material that is not see-through is a material that one cannot see through with an
19 unaided eye. The mesh materials 730 and 732 accommodate a ventilation of the pockets. The
20 bottom pocket with the mesh material 730 can have door zippers 740. I-rings are attached to the
21 front portion of the closed backpack to allow for attachments such as bungee cord to attach

1 additional items such as camping equipment or snowboards. An adjustable strap 734 is transversely
2 disposed near the middle section of the front portion of the closed backpack 710. The adjustable
3 strap 734 can secure bulky items such as butt-pads for ice hockey. The butt-pads for instance can
4 hook to the outside with the adjustable clasp 736. The adjustable strap 734 allows for the size of the
5 backpack 710 too be not excessively large since the adjustable strap can take care of extremely bulky
6 equipment. Since, the backpack 710 can be carried on the back of a user, an excessively large bag
7 may not be desirable. A handle 728 is attached to the top portion of the backpack 720 allowing
8 further flexibility for a user to carry the backpack 710. The backpack 710 can be closed from an
9 open position as seen in Fig. 8 to the closed position as seen in Fig. 10 with a zipper 738 or other
10 fastening means. The side walls 724 can be of a solid material that may or may not accommodate
11 ventilation or the side walls can be of a mesh material 725 as seen in Fig. 17 that accommodates a
12 ventilation of the inside of the bag 710 though the side walls. The mesh material 725 being on the
13 side walls (on both sides of the bag) is important because all the inner compartments 770 can be
14 ventilated properly. If both side walls are made of a material that allows ventilation like the mesh
15 material 725, then a cross vent is created to increase the ventilation of the inner compartments
16 (pockets) 770. Furthermore, because the material mesh 725 material is on the side walls, it is not
17 so prone to being worn out as if it was on the front or back side of the bag. The side walls 724
18 extend from each side of the bottom portion 782 of the back wall 780 of the backpack 710 where the
19 bottom portion 782 of the back wall 780 of the backpack 710 has a greater width than the top
20 portion 784 of the back wall 780 of the backpack 710. The side walls 724 form angles with the
21 extended portion 786 of the bottom back wall 782 of the backpack 710 accommodating a backpack

1 that closes all sides which then stop any loose items that get out of the compartments 770 from being
2 released from the bag 710.

3 **[0062]** Looking at Fig. 11, the backpack 710 (and also on bag 810) can have also a strap 752
4 secured to the top of the bag 710 that allows for clothes hangers to hang for jerseys or street clothes.

5 A 1 inch webbing 756 under 1 ½ inch webbing is added before stitching. A 1 inch webbing is placed
6 under top clasp before stitching. There must be enough slack allowed for attachment of hangers
7 holding jersey or other clothes. The total webbing length being added appears to be about 6 inches.

8 The 6 inches allows for one inch to be under the top webbing for securement and one inch to be
9 under other clasp strap 758 with four inches exposed allowing for enough slack to hang hangers for
10 jerseys and clothes. A clasp 754 is attached to the clasp strap 752 for hanging the jerseys or street
11 clothes.

12 **[0063]** Wheels can also be added to any of the above embodiments allowing a user to cart the bag.

13 The backpacks 210, 610, and 710 may especially have wheels on a bottom portion allowing for a
14 user to cart the backpacks 210, 610, and 710. Referring to Fig. 15, the backpack 910 is the same as
15 backpack 710 except that backpack 910 includes a pair of wheels 920 that allows for the backpack
16 910 to be transported on the ground by rolling the backpack along the ground or other surface by
17 pulling from the handle 940. The backpack 910 further includes a pair of straps 930 accommodating
18 a user to carry the backpack 910 on his or her back.

19 **[0064]** Referring to Fig. 19, straps 790 can be used to secure longer items 792 to sides of the bag
20 710. The straps 790 may include fasteners such as velcro, clasps and other means of attachment.

21 The straps 790 can be elastic allowing a user to slide items in the openings. Mesh pockets can also

